

Isuzu NPR 71K

GENERAL

TYPE

General Truck Type Rigid Truck

Wheel Configuration 4x2

Truck model NPR71K

DIMENSIONS

Axle distance (mm) 3,815

Rear overhang (mm) 1,710 / 1,875 Overall length (mm) 6,635 / 6,800

Chassis width (mm) 1,650

Overall height (mm) 2,225

Ground clearance (mm) 210

WEIGHTS

Maximum GVM (kg) 7000 Chassis weight (kg) 2645

ENGINE

Model 4HG1

Type Direct Injection, OHC

Number of cylinders 4

Fuel Diesel
Volume (cc) 4,570

Power (PS) 121 at 3,200 rpm

Max Torque 304 Nm at 1,600 rpm

Generator 24V-4.0kW

ISUZU STATE OF THE PROPERTY OF



AXLES AND SUSPENSION

FRONT

Axle type Steering (Reserve Elliot, I-beam)

Axle weight technical (kg) 3,100

REAR

Axle type Drive

Axle weight technical (kg) 5,000

SUSPENSION

Suspension Type Semi-elliptical leaf springs, hydraulic acting telescopic shock absorber



TIRES

Tire type Tube

Tire size 7.00R16 – 10

Tire quantity 7

BRAKES

Service Hydraulic dual circuit, Front: 2-leading and Rear: dual 2-leading

Parking Mechanical expanded type at rear of transmission

STEERING

Steering wheel position Left hand

Type Power Steering

Gear Ratio: 6.142

ELECTRICS

Electrical system 24V

Batteries 12V; 2x 90 Ah

Starter motor 4 Kw

INSTRUMENTS

Master cluster Speedometer km/h; Odometer km; RPM meter; Tachometer; Water temperature

gauge; Oil pressure gauge; Fuel gauge

Multi-function stitches direction lights; window wipers & window washer; electric horn

FINISHING

Cab color one-tone color paint (White)

Chassis color Black